Coast Guard, DHS § 133.175

full complement of persons and equipment.

- (e) Each rescue boat launching appliance must be fitted with a powered winch motor.
- (f) Each rescue boat launching appliance must be capable of hoisting the rescue boat when loaded with its full rescue boat complement of persons and equipment at a rate of not less than 0.3 meters per second (59 feet per minute).

[CGD 84-069, 61 FR 25304, May 20, 1996, as amended at 63 FR 52816, Oct. 1, 1998]

§ 133.170 Line-throwing appliance.

- (a) *General*. Each OSV must have a line-throwing appliance that is approved under approval series 160.031 or 160.040.
- (b) *Stowage*. The line-throwing appliance and its equipment must be readily accessible for use.
- (c) Additional equipment. Each OSV must carry the following equipment for the line-throwing appliance:
- (1) The equipment on the list provided by the manufacturer with the approved appliance.
 - (2) An auxiliary line that—
- (i) For an appliance approved under approval series 160.040, is at least 450 meters (1,500 feet) long;
- (ii) For an appliance approved under approval series 160.031, is at least 150 meters (500 feet) long;
- (iii) Has a breaking strength of at least 40 kiloNewtons (9,000 poundsforce); and
- (iv) Is, if synthetic, a dark color or certified by the manufacturer to be re-

sistant to deterioration from ultraviolet light.

§133.175 Survival craft and rescue boat equipment.

- (a) All rescue boat equipment must be as follows:
- (1) The equipment must be secured within the boat by lashings, storage in lockers or compartments, storage in brackets or similar mounting arrangements, or other suitable means.
- (2) The equipment must be secured in such a manner as not to interfere with any abandonment procedures or reduce seating capacity.
- (3) The equipment must be as small and of as little mass as possible.
- (4) The equipment must be packed in a suitable and compact form.
- (5) The equipment should be stowed so the items do not—
- (i) Reduce the seating capacity;
- (ii) Adversely affect the seaworthiness of the survival craft or rescue boat; or
- (iii) Overload the launching appliance.
- (b) Each rigid liferaft and rescue boat, unless otherwise stated in this paragraph, must carry the equipment specified for it in table 133.175 of this section. Each item in the table has the same description as in §199.175 of this chapter.

Note: Item numbers in the first column of Table 133.175 are not consecutive because not all of the items listed in section 199.175 are required on OSVs.

TABLE 133.175—SURVIVAL CRAFT EQUIPMENT

	ltem	Oceans		Coastwise	
Item No.		Rigid life- raft (SOLAS A Pack)	Rescue boat	Rigid life- raft (SOLAS B Pack)	Rescue boat
1	Bailer ¹	1	1	1	1
3	Boathook		1		1
4	Bucket ²		1		1
5	Can opener	3			
6	Compass		1		1
8	Drinking cup	1			
9	Fire extinguisher		1		1
10	First-aid kit	1	1	1	1
11	Fishing kit	1			
12	Flashlight	1	1	1	1
14	Heaving line	1	2	1	2
15	Instruction card	1		1	
17	Knife 1 3	1	1	1	1
18	Ladder		1		1
19	Mirror, signalling	1		1	